

DETAIL "G" SLIP COLLARS

ALTERNATE 12" (300mm) AND 6" (150mm) LENGTH P4100 SLOTTED UNISTRUT FACE DOWN AS SHOWN. SECURE ASSEMBLY TO LONG UNISTRUT MEMBER USING 3/8" (9mm) X 3/4" (19mm) LONG HD GALVANIZED BOLTS, WASHERS AND NUTS. THESE ASSEMBLIES CAN BE LONGER AND EXTEND OUT BEYOND FRAMEWORK TO SUPPORT ANY PERIMETER PLUMBING

SLIP COLLARS ARE 3" (75mm) LONG PIECES OF 2" (50mm) PVC OR ABS PIPE.

THESE ARE ATTACHED TO P4100 UNISTRUT USING #32 ALL STAINLESS STEEL GEAR CLAMPS THROUGH ADJACENT "SLOTS". SLOTTED UNISTRUT ALSO ALLOWS WATER TO DRAIN THROUGH FREELY.



SLIP COLLAR

STRAP SECURING HARDWARE THROUGH GRAVEL TO THE SCREEN MESH BELOW SEE DETAIL C

1.5" (37mm) PVC COUPLING

6" (150mm) P4100 UNISTRUT

12" (300mm) P4100 UNISTRUT

LONG UNISTRUT MEMBER

SLIP COLLAR ASSEMBLIES MUST BE POSITIONED TO ALLOW FREE MOVEMENT OF HEADER PIPES AND PVC PIPES. ALLOW FOR A MOVEMENT OF 1 INCH (25mm) FOR EVERY 30 FEET (9000mm) OF CONTINUOUS PLUMBING INCLUDING POWERSTRIP HEADER PIPES

PAINT ANY CUT UNISTRUT ENDS WITH ZINC BASED PAINT

HOT SUN INDUSTRIES LTD. Burnaby BC Canada 778-300-1803		FLAT ROOF MOUNTING	
		SLIP COLLAR ASSEMBLY POWERSTRIP PSG135 SOLAR COLLECTORS	
ECH/SC		NO. DESSIN / DWG NO.	GR/SIZE
DATE	JUNE 10, 2013	DWG BON 10 G	
PAR/BY	KEN WRIGHT		
VER/CHK			